



Direct thermal Printer

XP-58IIA

- Headlamp key design
- Support QR code printing
- Support IAP online upgrade
- Support print density adjustment



Model: XP-58IIA

Printing method	Direct thermal
Paper width	57.5±0.5mm
Print width	48 mm
Column capacity	384 dots/line
Interface	USB/USB+Bluetooth
Line spacing	3.75mm (Adjustable by commands)

Fonts Symbology

Character size	Afont A: 12x24, Font B: 9x17, CHN: 24*24
Extension character sheet	UPC-A/UPC-E/JAN13(EAN13) / JAN8(EAN8)/CODE39/ITE/ CODABAR / CODE93/CODE128/QR code PC347(Standard Europe) / Katakana / PC850(Multilingual)/ PC860(Portuguese) / PC863(Canadian-French)/PC865(Nordic) / West Europe / Greek / Hebrew/East Europe/Iran /WPC1252/PC866(Cyrillic #2)/ PC852(Latin2)/PC858/IranII/Latvian / Arabic / PT151(1251
Input buffer	128 Kbytes
NV Flash	1M bytes

Power

Power adaptor	Power adaptor
Power source	DC 9V/2A
Cash drawer	DC 12V/1A

Physical characteristics

Weight	0.45kg
Dimensions	138.77*122 * 93.3mm

Environmental Requirements

Work environment	Temperature (0-45°C) humidity(10-80%)
Storage environment	Temperature(-10-60°C) humidity (10-90%)

Realibility

Printer head life	50Km
-------------------	------

Software

Emulation	ESC/POS
Driver	Windows/JPOS/Linux/Android/Mac
SDK	iOS, Android, Windows