



XP-K200L/K260L


Thermal Receipt Printer

- Wall mount available;
- Support IAP update online
- Support QRcode, PDF417



XP-K200L/K260L

Thermal Receipt Printer



Printing	XP-K260L	XP-K260L	XP-K200L	XP-K200L
Printing method	Direct Thermal			
Paper width	79.5±0.5mm			
Print width	72mm			
Column capacity	576 dots/line or 512 dots/line			
Printing speed	260mm/s	260mm/s	200mm/s	200mm/s
Interface	USB+Serial+Lan	USB+Serial+Lan+WIFI	USB+Lan	Lan
Line spacing	3.75mm (Adjustable by commands)			
Column number	80mm paper: Font A - 42 columns or 48 columns/Font B - 56 columns or 64 columns/ Simplified/Traditional Chinese - 21 columns or 24 columns			
Character size	ANK, Font A: 1.5×3.0mm(12×24 dots) Font B: 1.1×2.1mm(9×17 dots) Simplified/Traditional Chinese:3.0×3.0mm(24×24 dots)			
Cutter				
Auto cutter	Partial			
Barcode Character				
Extension character sheet	PC347(Standard Europe) / Katakana / PC850(Multilingual) / PC860(Portugal) / PC863(Canadian) / PC865(Nordic) / West Europe / Greek / Hebrew / East Europe / Iran/WPC1252 / PC866(Cyrillic#2) / PC852(Latin2) / PC858 / IranII / Latvian / Arabic / PT151(1251)			
1D Barcode	UPC-A/UPC-E/JAN13(EAN13)/JAN8(EAN8)/CODE39/ITF/CODABAR/CODE93/CODE128			
2D Barcode	QR CODE / PDF417 (Except LAN)			
Input buffer	USB+Seria:64 Kbytes; USB+Lan:128 Kbytes	128 Kbytes		
NV Flash	256 Kbytes			
Power				
Power adaptor	Input: AC 110~240V, 50 ~ 60Hz, Output: DC 24V/2.5A			
Printer Input	DC 24V/2.5A			
Cash drawer	DC 24V/1A			
Physical characteristics				
Weight	1.0 Kg			
Dimensions	189.15*145.35*139.7mm(D*W*H)			
Environmental Requirements				
Work environment	Temperature (0 ~ 45℃) humidity(10 ~ 80%)			
Storage environment	Temperature(-10 ~ 60℃) humidity(10 ~ 90%)			
Reliability				
Cutter life	1.5 million cuts			
Printer head life	150Km			
Software				
Emulation	ESC/POS			
Driver	Windows/JPOS/Linux/OPOS/Android/Mac			
Utility	Windows & Linux test Utility			
SDK	iOS, Android, Windows			

